

O ENT

\* The above design is prototype. Product design is subject to change

# Enterprise Keypad Mobile Computer

# **EK43**0

# **The Ultimate Performance Combination Keypad/Touch Mobile**



os Android 10.x







**Operation Temp** -20°C to 50°C

Performance

Octa-Core Processor



Wireless Wi-Fi, Bluetooth

13MP Autofocus



**Battery** User Replaceable, Smart Battery







Display 4.3" WVGA (480 x 800)



Scanning 1D & 2D imager



**Drop Resistance** 

Multiple 1.8 m (6 ft) drops to concrete

### **Specification**

| Performance Characteristics |   |  |
|-----------------------------|---|--|
| CPU                         | Qualcomm Snapdragon SD660 2.2 GHz octa-core         |  |
| Operating System            | Android 10; Upgradeable to Android 14               |  |
| Memory                      | 4GB RAM / 32GB UFS<br>4GB RAM / 64GB UFS (Optional) |  |

#### **Physical and User Environment Characteristics**

| Display             | 4.3", WVGA, IPS (480 x 800), Corning® Gorilla® Glass   |
|---------------------|--|
| Dimensions & Weight | 210 x 76 x 37mm / 450g   |
| Touchpanel          | Dual input mode with finger, gloved finger and stylus  |
| Backlight           | LED Backlight  |
| Battery             | User replaceable Battery 3.6V, 6,800mAh / Smart Battery / Hot Swap mode support  |
| Expansion slot      | User accessible MicroSD with 32GB SDHC and up to 512GB SDXC  |
| SIM                 | 1 Nano SIM (Optional)  |
| Quick Charging      | Fast Charging (Full charge within 5 hours)   |
| Interface           | USB Type C Connector (USB 3.1), Bottom 8-pin / Rear 10-pin connector   |
| Drop spec.          | Multiple 6 ft./1.8 m drops to concrete across the operating temperature range per MIL-STD-810G Multiple drops from 2m (6.5ft) per MIL-STD 810G(Wood) at room temperature |
| Tumble spec.        | 3000 3.3 ft./1.0m tumbles; meets and exceeds IEC tumble specification  |
| Sealing             | IP65   |
| Temperature         | Operating: -20°C to 50°C / -4°F to 122°F   |
| Humidity            | 5% to 95% RH (Non-condensing)  |
| Keypad & Button     | Numeric / Function Numeric (Optional) / Alpha Numeric (Optional) Dual-action side scan triggers  |

#### Communications & Data Capture

| Communications & Data Capture |   |
|-------------------------------|---|
| Communications                | LTE (Optional), IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc (Wi-Fi™ certified IPv4, IPv6, 2x2 MU-MIMO) Class 2, Bluetooth v5.0 with BR/EDR and Bluetooth Low Energy (BLE) Support |
| Camera                        | Rear : 13MP, LED flash (Optional) / Front : 5MP fixed focus (Optional)  |
| Barcode Scanning              | 1D & 2D Imager / 1D Laser, Long Range Scanner (Optional)  |
| NFC                           | ISO 14443 Type A and B; FeliCa, and ISO 15693 cards, P2P mode and Card Emulation via Host (HCE) support   |
| Accessory                     | 1SC/4SC Cradle, 4SC Battery Charger, Trigger Handle, Hand Strap, Holster, Stylus, Protective Film   |

\* Specifications are subject to change upon manufacturer's condition without notice.

## **Industry & Applications**

#### Warehousing / Distribution

- Warehouse management
- Picking and put-away
- Return processing
- Voice-directed applications
- EDI transactions
- Inventory management

#### Manufacturing

- Inventory management
- Supply-line replenishment
- Safety testing
- Parts tracking

#### Retail

- Backroom warehouse management
- Store receiving
- Inventory management
- In-store communications

#### Transportation

- Electronics Toll collection system

#### BOS™ Solutions & Software

- BOS™ Provisioning; Staging; Kiosk; Virtual Key; Enterprise Keyboard
- BOS™ VoIP
- BOS™ PTT, PTT Essential
- BOS™ Wi-Fine™ (WiFi analyze application)
- BOS™ EMM
- BOS™ OTA
- BOS™ OEMConfig

#### 3'rd Party Solutions Integration

- EMM: Airwatch, MobileIron, Mobicontrol, IBM Mass360, XenMobile
- PTT : ESChat, Zello, IMPTT, EveryTalk, AirPTT