

sewoo

Desktop Label Printer

LK-B24



- Fast Print Speed : 5 ips
- Excellent Compatibility
- Stable & Reliable label printing
- Easy to use and maintenance
- Ultra Compact and Lightweight
- Thermal transfer and Direct thermal printing
- Support label design software "Label Cooker"



WiFi



Bluetooth



Barcode



Durable



Fast
Speed



Easy
Loading



Compact
Design



Easy
Replacement

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Thermal transfer and Direct thermal

Print Speed
Up to 5ips(127mm/sec)

Print Width
Up to 4.1”(104mm)

Resolution
203 dpi (8dots/mm)

Memory
1MB Main Flash, 16 SDRAM,
8MB Font flash

Sensor
Gap, Black mark, Cover open,
Ribbon encoder

Power
Type : External SMPS
AC : 100~240Vac, 1.5A, 50/60Hz
DC : 24Vdc/2.5A

Auto-cutter(Optional)
Type : Guillotine
Life : 200,000 Cuts, Max 20 cycle/1 min



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
8.5”x9.8”x6.3”
(216.2 x 250.5 x 160.6 mm)

Weight (Kg)
4.1lb(1.9kg)



MEDIA CHARACTERISTICS

Media Type
Roll, Fanfold, Blackmark,
Continuous, Gap, Notch Sensor

Media Width
0.7”~4.4”(20~114mm)

Media Core Diameter
Ø 1”(25.4mm)
Ø 1.5”(38.1mm)

Media Roll Diameter
Internal: Ø 1”(25.4mm) or
Ø 1.5”(38.1mm)
External: Ø 5”(127mm)

Thickness
0.065~0.20mm



OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 104°F(0 ~ 40°C)

Operating Humidity
10 ~ 90%

Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity
10 ~ 90%



BARCODES

1D
Code39, Code128 with subsets
A/B/C/Auto, UCC/EAN-128,
Code93, Codabar, Interleaved 2
of 5, UPC-A, UPC-E, UPC-A and E
with 2 or 5 digit extension, EAN-8,
EAN-13, EAN-8 and 13 with 2 or 5
digit extensions, Postnet, Plessey,
MSI-3, German Post CodeLogmars,
Code11, UPC_Interleaved 2 of 5,
Industrial 2 of 5, Standard 2 of 5,
Planet, ANSI, Logmars

2D
MaxiCode, PDF 417, Data Matrix,
QR Code, MicroPDF417, AZTEC,
Code 49, CODABLOCK, RSS



SOFTWARE

Emulations
EPL II, ZPL II Command compatible

Drivers
Windows Driver
Linux Driver
Mac Driver

SDK
Windows SDK
Android SDK
iOS SDK



INTERFACES

Standard
USB, Serial(RS-232C), Ethernet



CERTIFICATIONS

FCC, KCC, UL/cUL, CE, CB



FONTS / GRAPHICS

EPL II
6 bitmapped
8x12, 10x16, 12x20, 14x24,
32x48, 24x24(KSC5601)

ZPL II
9 bitmapped
5×9, 7×11, 10×18, 10x18, 15×28,
13×26, 40×60, 13x21, 24x24
2 smooth scalable(English, Korean)



ACCESSORIES

Standard
Power Cord, Power Supply,
Interface Cable(USB)

Optional
External Paper Supply

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com

